


B-PIR




- Fitted with Infra-red sensor activated by presence.
- Timer (electronic timer adjustable from 3 to 15 minutes).
- White finishing.
- Plastic housing and impeller.
- 230 V, 50 Hz motor, protection IP-X4, insulation class B as thermal cut out, ambient temperature max. 40°C.



SHORT TUBE

CODE	MODEL	VERSION	Ø (mm)	Voltage (V)	Speed (r.p.m)	Input Power (W)	Maximum AirFlow (m3/h - l/s)	Sound Pressure Level dB(A)	Weight (Kg)	Units per Box
00913000	B-10 PIR		100	230	2.500	15	98	41	0,6	4

DIMENSIONS mm



	Ø A	B	C	D
B-10 PIR	98	150	42	35

Axial fans for bathrooms with short tube for wall, ceiling and glass (using Glass Kit accessory).

B




- White finishing.
- Plastic housing and impeller.
- Fitted with 230 V 50 Hz motors, IP-X4 protection and class B as standard.
- Neon light sensor in humidistat versions.

SHORT TUBE

CODE	MODEL	VERSION	Ø (mm)	Voltage (V)	Speed (r.p.m)	Input Power (W)	Maximum AirFlow (m3/h - l/s)	Sound Pressure Level dB(A)	Weight (Kg)	Units per Box
TIMER SERIES										
00911000	B-10 T	●	100	230	2.500	15	98	41	0,6	10
STANDARD SERIES										
00910000	B-10	●	100	230	2.500	15	98	41	0,6	10
00920000	B-12	●	120	230	2.450	20	190	43	0,85	5
00930000	B-15	●	150	230	2.100	25	320	43	0,95	5

DIMENSIONS mm



	Ø A	B	C	D
B-10	98	150	42	35
B-12	118	180	45	44
B-15	148	209	60	45

Versions



STANDARD
In combination with light, fans switches on.



TIMER
Electronic timer adjustable from 3 to 15 minutes.