

Perimetral bathroom fans, with unique automatic shutter system.

X-MART MATIC / X-MART MATIC INOX




- Automatic shutter system.
- Recessed and design of a new generation.
- **QUICK FIX GRIP**, exclusive mounting system
- Backdraught shutters incorporated.
- Front cover easy to dismantle without using any tools, easy cleaning.
- 230 V, 50 Hz motors, protection **IP-X4** insulation class **B** and thermal cut out, ambient temperature max. 40°C.
- Plastic housing and impeller and led.
- Finishes: White / Stainless Steel.



CODE	MODEL	VERSION	Ø (mm)	Voltage (V)	Speed (r.p.m)	Input Power (W)	Maximum AirFlow (m3/h - l/s)	Sound Pressure Level dB(A)	Weight (Kg)	Units per Box
HYGRO SERIES										
01047000	X-MART 10 MATIC INOX H	●	100	230	2.500	15	98	38	0,78	5
01057000	X-MART 12 MATIC INOX H	●	120	230	2.450	20	190	40	0,98	5
01067000	X-MART 15 MATIC INOX H	●	150	230	2.100	25	320	42	1,14	5
TIMER SERIES										
01016000	X-MART 10 MATIC T	●	100	230	2.500	15	98	38	0,65	10
01026000	X-MART 12 MATIC T	●	120	230	2.450	20	190	40	0,82	5
01046000	X-MART 10 MATIC INOX T	●	100	230	2.500	15	98	38	0,78	10
01056000	X-MART 12 MATIC INOX T	●	120	230	2.450	20	190	40	0,98	5
01066000	X-MART 15 MATIC INOX T	●	150	230	2.100	25	320	42	1,14	5
STANDARD SERIES										
01015000	X-MART 10 MATIC	●	100	230	2.500	15	98	38	0,65	10
01025000	X-MART 12 MATIC	●	120	230	2.450	20	190	40	0,82	5
01035000	X-MART 15 MATIC	●	150	230	2.100	25	320	42	0,97	5
01045000	X-MART 10 MATIC INOX	●	100	230	2.500	15	98	38	0,78	10
01055000	X-MART 12 MATIC INOX	●	120	230	2.450	20	190	40	0,98	5
01065000	X-MART 15 MATIC INOX	●	150	230	2.100	25	320	42	1,14	5

DIMENSIONS mm



	Ø A	B	C	D
X-MART MATIC 10	98	150	87	38 _{max.}
X-MART MATIC 12	118	170	101	38 _{max.}
X-MART MATIC 15	148	194	120	38 _{max.}

Versions



STANDARD

In combination with light, fans switches on.



TIMER

Electronic timer adjustable from 3 to 15 minutes.



HYGRO

Adjustable humidity detector from 40% to 90%, and adjustable electronic timer from 0 to 15 minutes.