

# Crystal-Right™ Silica Crystals

### The best product for problem water ...

Crystal-Right™ silica crystals are a natural choice for today's water conditioning systems. No other product does so much to condition problem water in a single pass.

These "zeolite" crystals come from a sodium aluminosilicate carefully produced and processed by Mineral-Right using an exclusive technology. Through its unique crystalline structure, Crystal-Right™ provides superior removal of hardness, iron and manganese while raising pH levels of acidic water at the same time.

Unlike round, resin beads, Crystal-Right™ crystals provide better filtration, and are thoroughly cleaned by backwashing faster than ordinary resins without loss of product.

Explore the many advantages of a single-pass, single-system product that is setting new industry standards. Your dealers and customers will be impressed.



## ■ Crystal-Right™ 100 Silica Crystals (CR 100)

For removing hardness, iron, manganese and raising pH

## ■ Crystal-Right<sup>™</sup> 200 Silica Crystals (CR 200)


Highest capacity for removing hardness, iron and manganese


#### Crystal-Right™ Silica Crystals can help you build a better water conditioning system:

- removes iron, manganese and hardness in a single pass
- raises pH levels in acidic water
- reduces ammonia
- provides superior filtering of particles and turbidity
- higher backwash flow removes suspended particles more thoroughly
- chlorinating Crystal-Right™ sanitizes the bed and holds a chlorine residual that kills bacteria
- can be chlorinated without breakdown or damage to product
- shipped in convenient 28,3 litre, 22,7 kg bags.

		Sl	JGG	ESTE	D RE	GEN	ERA	10IT	N PR	OGR	MAS	ME			
LITRES CRYSTAL- RIGHT <sup>IM</sup>	pH RANGE		TOTAL IRON & MANGANESE (mg/l)		HARDNESS RANGE (mg/l)		BACK- WASH (minutes)		BRINE & RINSE (minutes)		BRINE & DRAW (I/min.)		BACK- WASH (I/min.)		
	CR 100	CR 200	CR 100	CR 200	CR 100	CR 200	CR 100	CR 200	CR 100	CR 200	CR 100	CR 200	CR 100	CR 200	SIZE (in.)
*28	6+	7+	8	8	51-684	51-1369	16	12	72	72	1,5	1,5	15	12	10x44
*42	5,7+	7+	10	10	51-684	51-1369	16	12	90	90	1,5	1,5	15	12	10x54
*71	5,7+	7+	15	15	51-684	51-1369	16	12	90	90	3,0	3,0	27	21	13x54

 <sup>\*</sup> The use of Crystal-Right™ requires a minimum water hardness of 51 mg/l and a minimum of 80 mg/l Total Dissolved Solids (T.D.S.).
\* Crystal-Right™ requires a backwash flow rate of 15 to 20 m/hr.





© 2002 Water-Right, Inc. All rights reserved. Crystal-Right is a registered trade name of Mineral-Right, Inc.